



**NOTES:**

1. THE HOLE FOR THE MONUMENT SHALL BE CUT AFTER THE NEW PAVEMENT HAS BEEN CONSTRUCTED. THE UPPER 3" OF THE MONUMENT ENCASEMENT SHALL BE SHAPED TO A TRUE DIAMETER OF 8-INCH. CLASS "C" CONCRETE SHALL BE USED FOR THE ENCASEMENT. THE BRONZE MONUMENT WILL BE SET SIMULTANEOUSLY WITH THE POURING OF CONCRETE IN THE ENCASEMENT.
2. THIS MONUMENT TO BE USED PRIMARILY LOCAL ACCESS STREETS IN ASPHALT CONCRETE PAVEMENT.
3. BRASS CAP SHALL BE "BERNTSEN RB SERIES" OR BRASS PLUG MARKER. FERROUS METER MUST BE ATTACHED TO CAP.
4. CONCRETE TO BE PLACED ON A FIRM UNYEILDING FOUNDATION. FERROUS METER MUST BE ATTACHED TO CAP.

<b>TOWN OF FRIDAY HARBOR</b>			
<b>CAST IN PLACE CONCRETE SURFACE MONUMENT</b>			
APPROVED: <i>C. King</i> TOWN ADMINISTRATOR		1/16/97 DATE	DWG. NO. 4-22
DATE: 1/16/97	DRWN: E.S.T.	CHKD: T.A.N.	SCALE: NO SCALE